

15A NCAC 07H .1705 SPECIFIC CONDITIONS

(a) Temporary Erosion Control Structures in the Ocean Hazard AEC.

- (1) Permittable temporary erosion control structures shall be limited to sandbags placed landward of mean high water and parallel to the shore.
 - (2) Temporary erosion control structures as defined in Subparagraph (1) of this Paragraph may be used to protect only imminently threatened roads and associated right of ways, and buildings and their associated septic systems. A structure is considered imminently threatened if its foundation, septic system, or right-of-way in the case of roads is less than 20 feet away from the erosion scarp. Buildings and roads located more than 20 feet from the erosion scarp or in areas where there is no obvious erosion scarp may also be found to be imminently threatened when the Division determines that site conditions, such as a flat beach profile or accelerated erosion, increase the risk of imminent damage to the structure.
 - (3) Temporary erosion control structures shall be used to protect only the principal structure and its associated septic system, but not appurtenances such as pools, gazebos, decks or any amenity that is allowed under 15A NCAC 07H .0309 as an exception to the erosion setback requirement.
 - (4) Temporary erosion control structures may be placed waterward of a septic system when there is no alternative to relocate it on the same or adjoining lot so that it is landward of or in line with the structure being protected.
 - (5) Temporary erosion control structures shall not extend more than 20 feet past the sides of the structure to be protected except to align with temporary erosion control structures on adjacent properties, where the Division has determined that gaps between adjacent erosion control structures may result in an increased risk of damage to the structure being protected. The landward side of such temporary erosion control structures shall not be located more than 20 feet waterward of the structure to be protected or the right-of-way in the case of roads. If a building or road is found to be imminently threatened and at increased risk of imminent damage due to site conditions such as a flat beach profile or accelerated erosion, temporary erosion control structures may be located more than 20 feet waterward of the structure being protected. In cases of increased risk of imminent damage, the location of the temporary erosion control structures shall be determined by the Director of the Division of Coastal Management or the Director's designee.
 - (6) Temporary erosion control structures may remain in place for up to eight years for a building and its associated septic system, or a bridge or a road. The property owner shall be responsible for removal of any portion of the temporary erosion control structure exposed above grade within 30 days of the end of the allowable time period.
 - (7) For purposes of this Rule, a community is considered to be actively pursuing a beach nourishment or an inlet relocation or stabilization project if it:
 - (A) has an active CAMA permit, where necessary, approving such project;
 - (B) has been identified by a U.S. Army Corps of Engineers' Beach Nourishment Reconnaissance Study, General Reevaluation Report, Coastal Storm Damage Reduction Study, or an ongoing feasibility study by the U.S. Army Corps of Engineers and a commitment of local or federal money, when necessary; or
 - (C) has received a favorable economic evaluation report on a federal project; or
 - (D) is in the planning stages of a project designed by the U.S. Army Corps of Engineers or persons meeting applicable State occupational licensing requirements and initiated by a local government or community with a commitment of local or state funds to construct the project or the identification of the financial resources or funding bases necessary to fund the beach nourishment or inlet relocation or stabilization project.
- If beach nourishment, inlet relocation or stabilization is rejected by the sponsoring agency or community, or ceases to be actively planned for a section of shoreline, the time extension is void for that section of beach or community and existing sandbags shall be subject to all applicable time limits set forth in Subparagraph (6) of this Paragraph.
- (8) Once a temporary erosion control structure is determined by the Division of Coastal Management to be unnecessary due to relocation or removal of the threatened structure, it shall be removed by the property owner to the maximum extent practicable within 30 days of official notification from the Division of Coastal Management, regardless of the time limit placed on the temporary erosion control structure. If the temporary erosion control structure is determined by the Division of Coastal Management to be unnecessary due to the completion of a storm protection project

constructed by the U.S. Army Corps of Engineers, a large scale beach nourishment project, or an inlet relocation or stabilization project, any portion of the temporary erosion control structure exposed above grade shall be removed by the permittee within 30 days of official notification by the Division of Coastal Management regardless of the time limit placed on the temporary erosion control structure.

- (9) Removal of temporary erosion control structures is not required if they are covered by sand. Any portion of a temporary erosion control structure that becomes exposed above grade after the expiration of the permitted time period shall be removed by the property owner within 30 days of official notification from the Division of Coastal Management.
 - (10) The property owner shall be responsible for the removal of remnants of all portions of any damaged temporary erosion control structure.
 - (11) Sandbags used to construct temporary erosion control structures shall be tan in color and 3 to 5 feet wide and 7 to 15 feet long when measured flat. Base width of the structure shall not exceed 20 feet, and the total height shall not exceed 6 feet, as measured from the bottom of the lowest bag.
 - (12) Soldier pilings and other types of devices to anchor sandbags shall not be allowed.
 - (13) Excavation below mean high water in the Ocean Hazard AEC may be allowed to obtain material to fill sandbags used for emergency protection.
 - (14) An imminently threatened structure may be protected by a temporary erosion control structure only once regardless of ownership, unless the threatened structure is located in a community that is actively pursuing a beach nourishment project, an inlet relocation or stabilization project in accordance with Subparagraph (7) of this Paragraph. Existing temporary erosion control structures may be permitted for additional eight-year periods provided that the structure being protected is still imminently threatened, the temporary erosion control structure is in compliance with requirements of this Subparagraph, and the community in which it is located is actively pursuing a beach nourishment or an inlet relocation or stabilization project in accordance with Subparagraph (7) of this Paragraph. In the case of a building, a temporary erosion control structure may be extended, or new segments constructed, if additional areas of the building become imminently threatened. Where temporary structures are installed or extended incrementally, the time period for removal under Subparagraph (6) or (7) of this Paragraph shall begin at the time the initial erosion control structure is installed. For the purpose of this Rule:
 - (A) a building and its associated septic system shall be considered as separate structures; and
 - (B) a road or highway shall be allowed to be incrementally protected as sections become imminently threatened. The time period for removal of each contiguous section of sandbags shall begin at the time that section is installed in accordance with Subparagraph (6) or (7) of this Paragraph.
 - (15) Existing temporary erosion control structures may be repaired or replaced within their originally permitted dimensions during the time period allowed under Subparagraph (6) or (7) of this Paragraph.
- (b) Erosion Control Structures in the Estuarine Shoreline, Estuarine Waters, and Public Trust AECs. Work permitted by this Rule shall be subject to the following limitations:
- (1) The erosion control structure shall be located no more than 20 feet waterward of the imminently threatened structure. If a building or road is found to be imminently threatened and at increased risk of imminent damage due to site conditions such as a flat shore profile or accelerated erosion, temporary erosion control structures may be located more than 20 feet waterward of the structure being protected. In cases of increased risk of imminent damage, the location of the temporary erosion control structures shall be determined by the Director of the Division of Coastal Management or the Director's designee.
 - (2) Fill material used in conjunction with emergency work for storm or erosion control in the Estuarine Shoreline, Estuarine Waters, and Public Trust AECs shall be obtained from an upland source.
- (c) Protection, Rehabilitation, or Temporary Relocation of Public Facilities or Transportation Corridors. This permit authorizes only the immediate protection or temporary rehabilitation or relocation of existing public facilities. Long-term stabilization or relocation of public facilities shall be consistent with local governments' post-disaster recovery plans and policies which are part of their Land Use Plans.
- (1) Work permitted by this general permit shall be subject to the following limitations:

- (A) no work shall be permitted other than that which is necessary to protect against or reduce the imminent danger caused by the emergency or to restore the damaged property to its condition immediately before the emergency;
- (B) the erosion control structure shall be located no more than 20 feet waterward of the imminently threatened structure or the right-of-way in the case of roads. If a public facility or transportation corridor is found to be imminently threatened and at increased risk of imminent damage due to site conditions such as a flat shore profile or accelerated erosion, temporary erosion control structures may be located more than 20 feet waterward of the facility or corridor being protected. In cases of increased risk of imminent damage, the location of the temporary erosion control structures shall be determined by the Director of the Division of Coastal Management or the Director's designee in accordance with Subparagraph (a)(1) of this Rule;
- (C) any fill materials used in conjunction with emergency work for storm or erosion control shall be obtained from an upland source except that dredging for fill material to protect public facilities or transportation corridors shall be considered in accordance with standards in 15A NCAC 07H .0208; and
- (D) all fill materials or structures associated with temporary relocations which are located within Coastal Wetlands, Estuarine Water, or Public Trust AECs shall be removed after the emergency event has ended and the area restored to pre-disturbed conditions.

History Note: Authority G.S. 113-229(cl); 113A-107(a),(b); 113A-113(b); 113A-115.1; 113A-118.1; Eff. November 1, 1985;
Amended Eff. April 1, 1999; February 1, 1996; June 1, 1995;
Temporary Amendment Eff. July 3, 2000; May 22, 2000;
Amended Eff. April 1, 2019; May 1, 2013; May 1, 2010; August 1, 2002;
Readopted Eff. July 1, 2022.